

产品规格表

产品描述:



外形尺寸 (mm)	
高度:	1150
宽度:	1000
长度:	1200
叉孔宽度:	400
叉孔高度:	85
叉车开口:	100

注:
请确认内装物与包装容器的化学相容性，可提供其他密封材质供选择

1000L中型散装容器，全钢托盘，蝶阀，球阀

IBC

结构:	全钢型			
公称/满口容积 (L) :	1000	≥1058		
核定重量 (kg) :	56±1			
堆码重量 (kg) :	1658			
最大允许重量 (kg) :	1958			
最大允许密度 (g/m) :	1.9			
UN编号:	31HA1/Y/XXXX/CN/C231609/3525/1958/1058L/58kg/100 kPa			
内容器				
材质:	高密度聚乙烯			
制造方法:	挤出吹塑成型			
内容器重量 (kg) :	14±0.5			
灌装口径 (mm) :	143			
顶盖				
类别	大盖	大盖 密封圈	小盖	小盖 密封圈
材质:	HDPE	EPDM	PP	EVA
透气装置 (可选) :	双向透气膜			
阀门				
材质:	PE/PP			
密封垫圈材质:	EPDM/ PE/ FKM			
内径 (mm) :	50/80			
托盘与拉杆				
分类	托盘		拉杆	
材质:	镀锌钢 DX53D		镀锌钢 DC51D	
加工方法:	焊接		焊接	
框架				
材质:	镀锌钢管 DC51D			
加工方法:	钢管焊接，弯管机成形			
其他				
阀门开启保险、安全外盖、铝箔密封、放料弯管				

Product Specification Sheet

Article description :		1000L Composite IBCs				
 		IBC				
		Construction :		Window pallet of steel		
		Nominal/brimful(L) :		1000		≥1058
		Tare weight (kg) :		56±1		
		Stacking weight (kg) :		1658		
		Max. weight (kg) :		1958		
		Max.density (g/m) :		1.9		
		UN approval :		31HA1/Y/XXXX/CN/C231609/3525/1958/1058L/58kg/100 kPa		
		Inner receptable				
		Material :		HDPE		
Fabrication :		Extrusion blow molded				
weight (kg) :		14±0.5				
Inner opening diameter (mm) :		143				
Top lid						
category		Lid	L-gasket	Bung	B-gasket	
Material :		HDPE	EPDM	PP	EVA	
Gassing device:		Press-Fit Vents				
Discharge valve						
Material :		PE/PP				
Gasket material:		EPDM/PE/FKM				
Inner diameter (mm) :		50/80				
Pallet and top bar						
Type		Pallet		Top bar		
Material :		Galvanized steel DX53D		Galvanized steel DC51D		
Fabrication :		Welded		Welded		
Cage						
Material :		Galvanized steel DC51D				
Fabrication :		Tube cage welded				
Miscellaneous / specialties						
Protector, sccure cap, discharge sealed Al film, discharge tube						

dimension (mm)	
Height :	1150
Width:	1000
Length:	1200
Pallet hole Width:	400
Pallet hole height:	85
Fork opening:	100

Notice:

Be aware of resistance of used gasket material against filling goods. Other gasket materials are available